together with local, railway and other cesses, if any, on the full lease amount at the rate prevailing in the district. In default, the deposit already made will be forfeited and the right resold. Such resale will be at the risk of the defaulting purchaser who will be liable to make good any loss that may result to Government by it, but will have no claim to any surplus accruing therefrom. Such losses shall be recoverable as an arrear of land revenue.

10. If the tender is not accepted by the authority concerned, all moneys paid will be refunded to the party.

For other details and conditions of the lease, please see detailed Notification No. E. 272-1077-34, dated 8th April 1935, published by the Chief Conservator of Forests in Mysore in the *Mysore Gazette*, dated 18th April 1935 (pages 873 to 875 of Part VI).

M. G. VENKATA RAO,
District Forest Officer.

KADUR FOREST DIVISION.

Abstract Notification dated the 19th March 1936.

The attention of the public is invited to the detailed Notification calling for tenders for weighing out of rough and assorted Sandalwood in Chikmagalur Sandal Koti in connection with the annual stock-taking printed on pages 414-415, Part VI of the *Mysore Gazette*, dated 26th March 1936.

A. V. KESAVIENGAR,
District Forest Officer.

ENGINEERING DEPARTMENT

BANGALORE DIVISION.

Notification dated 28th March 1936.

Notice is hereby given that sealed tenders will be received at the Office of the Executive Engineer, Bangalore Division, up to 2 P.M. on 15th April 1936, for constructing a building for the Urdu Diara Primary Girls' School at Channapatna. An approximate estimate of quantities is given below. These quantities are not guaranteed. The work should be completed by the end of August 1936.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Bangalore, between the hours of 11 A.M. and 5 P.M.

3. Tender should be submitted on printed forms which may be obtained from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed:—

4. Each tender must be accompanied by a deposit of rupees six hundred in cash or Government Promissory Notes, as earnest money, and be superscribed "Tender for constructing a building for the Urdu Diara Primary Girls' School at Channapatna" in default of which tenders will be rejected.

5. The final acceptance of any tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond, in default of which his tender will be considered cancelled, and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the acceptance or rejection of a tender will receive any reply.

8. On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced on any account.

10. Rates for non-tendered and non-estimated items shall be as per schedule rates of the department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for contractor's profit.

11. In all matters not specifically provided for and in all matters of dispute about rates, quantities, measurements, quality of works, etc., and in all disputes of any kind, the decision of the Executive Engineer will be final and legally binding.

12. Quotations must be given in words as well as in figures and they must be in specific term of unit shown against each item of work. Any quotation quoted at so much percentage less or more than estimated rate will not be accepted.

Approximate quantity required for the construction of a building for the Urdu Diara Girls' School at Channapatna.

No.	Items of work	Unit	Quantity	Rate sanctioned	Rate quoted in	
					Figures	Words
				Rs. a. p.		
1	Earthwork excavation for foundation and filling in basement	C.yd.	245	0 3 6		
2	Burnt stone jelly concrete in lime mortar for foundation	C.ft.	1,757	0 3 9		
3	Size stone in clay with bond stones for every 6 feet in each layer for foundation and basement ..	,,	4,797	0 4 0		
4	Burnt brick in clay superstructure ..	,,	4,368	0 3 6		
5	Burnt brick in mortar for sides of doors and windows and top of walls	,,	1,337	0 4 0		
6	Burnt stone slabs 6″ thick one line dressed and fixed in mortar ..	S.ft.	1,065	0 4 0		
7	Burnt stone slabs 6″ thick two line dressed and fixed in mortar ..	,,	270	0 6 0		
8	Mysore teakwood doors 4′×10′ including top glazed ventilators with frames 4½″×4″ in section shutters 1½″ thick panelled and clamps and iron fittings, etc., complete ..	,,	560	1 12 0		
9	Mysore teak wood windows 4′×7½′, 6′×7½′ and 2′×7½′ including top glazed ventilator with frames 4½″×4″ in section ¾′ dia. iron bars and 1¼″ thick panelled shutters outside and galzed shutters inside and iron clamps and fittings, etc., complete	,,	630	3 0 0		
10	Mysore teak wood glazed ventilators with iron bars cotton rope hooks, etc., complete	,,	64	1 2 0		
11	Rolled steel girders including hoisting, fixing, painting, etc., complete ..	Cwt.	39	11 8 0		
12	Reinforced brick concrete terraced roofing with two courses of flat tiles and plastering the top and bottom ceiling, etc., complete as per specification	Sqr.	30·69	70 0 0		
13	Block cornice with brick in mortar including plastering, whitewashing, etc., complete as per design ..	R.ft.	267	0 4 0		
14	Burnt brick in mortar parapet wall with whitewashing, etc., complete as per design	,,	265	0 14 0		
15	Plastering with lime mortar ¾″ thick in 2 coats	Sqr.	117·52	3 0 0		
16	Whitewashing	Sqr.	117·52	0 3 9		
17	Cement pointing to basement ..	,,	9·24	3 4 0		
18	Silicate painting to doors and windows, grey colour	,,	27·59	3 8 0		
19	Flooring with 1½″ cement concrete on 3″ stone jelly concrete in lime mortar bed and plastered with ½″ thick cement mortar mixed with red ochere and cut into squares, etc., complete	,,	25·99	22 0 0		
20	Providing and fixing 22′ gauge 3″ diameter water spouts	R.ft.	256	0 6 0		

M. A. SRINIVASACHARI,
Executive Engineer.